





Bent roof-crossing masts

art. 07-808/A PALO CURVO CON ZANCA A MURARE

Bent mast equipped with two spaced fixing plates and two wall supports.

The tubes are made of steel, hot dip galvanized to ensure high quality and durability. The protection of the zinc cladding is of 50/85 microns thick.



The measures are in mm, unless otherwise specified.

Dimensional and thickness tolerances are allowed by the regulations that establish the quality of the raw materials used.

| Anti-al- | | 07.000/4 | 0 | | | | \sim | × × | |
|-------------------|--------------------|--|------------|-----|-------|----|--------|---------|-----|
| Articolo Sigla | | 07-808/A PALO CURVO CON ZANCA A MURARE | | 40 | 140 | | (1) | X) | |
| | | | († | (*) | | | | | 220 |
| POLE | | | (III) | | 1 | | -lil | | |
| Ø | mm | 38 | | 95 | | | | Ψ | |
| Thickness | mm | 2 | | - | | | 180 | | |
| Lenght | m | 1,8 | | | | | | | |
| FIXING PLATES | | | | | 200 | | 1 | | |
| Distances | mm | 500; 140 | | | -342) | | | | |
| Dimensions | mm | 126x40 | | | | | | | |
| Thickness | mm | 4 | | | | | | | |
| For masts Ø | mm | 25 ÷ 60 | | | | | | | |
| Screws | | QST 8x60 mm | I | 0 | 3 | | -11 | | |
| Spacers | mm | 50 | | | | | | | |
| BENT | | | | | | | | | |
| Type of bent | | fixed | | | | | | | |
| Bending radius | | 180° | | | | | | | |
| Ø | mm | 38 | | | 8 | | | | |
| Thickness | mm | 2 | | | 1800 | | 1 | | |
| WALL MOUNT | | | | | | 02 | Ø38 | X2 | |
| Туре | | "L" support | | | | | | | |
| Dimensions | mm | 250x15x30 | | | | | | | |
| Packaging | | | | | | | | | |
| Packaging Di | mensions LxWxH (mm | ı) Weight (Kg) | - | | | | - | 1 | 3 |
| Single | 400x130x1800 | 5,5 | | | | | 1 | | |
| | | Per serraggio tubi da Ø25 a Ø60 | | | | | T | | |
| | 126 | | | | | 50 | | 250 | 1 |
| | | | | | | Ť | Rev. 1 | 11.2016 | |

