



Multifeeds

MF series

art. 11-092 MF3 PO G



Ideal for the reception of several satellites because it allows the use of 3 LNB with a single dish.

The distance between two satellites is expressed in degrees.

If the distance in degrees between the two satellites isn't change, with the increase of the dish diameter also increases the distance between the focal point and the secondary focal points.

It is sold already assembled. Feeder clamps for LNB Ø 23 are supplied.

Code	11-092	
Item	MF3 PO G	
No. LNB supports	3	
Ø LNB supports	mm	23 and 40
Fixing base material	Steel	
LNB supports material	Plastic	
Dimensions (LxWxH)	mm	240x75x100
Packaging dimensions (LxWxH)	mm	300x170x60
Packaging weight	Kg	0,40

Compatibility with offset Offel dishes

Dishes series	PO 65 G	PO 78 G	PO 85 G	PO 100 G	PO 120 G	PO 150 G
Distance between two satellites receivable by placing two adjacent LNBs to the minimum possible distance	6°	6°	5°	5°	3°	3°
Distance between two satellites receivable by placing the two LNBs at the edges to the maximum possible distance	20°	18°	16°	13°	10°	8°

Usable with the dishes shown below:



Aluminium, Ø 65 mm

Cod. 11-060 PO 65 G
Cod. 11-061 PO 65 G/R
Cod. 11-062 PO 65 G/G



Aluminium, Ø 78 mm

Cod. 11-069 PO 78 G
Cod. 11-070 PO 78 G/R
Cod. 11-071 PO 78 G/G



Aluminium, Ø 85 mm

Cod. 11-076 PO 85 G
Cod. 11-077 PO 85 G/R
Cod. 11-078 PO 85 G/G



Aluminium, Ø 100 mm

Cod. 11-100 PO 100
Cod. 11-101 PO 100 G/G
Cod. 11-102 PO 100 G/R



Aluminium, Ø 120 mm

Cod. 11-120 PO 120 G
Cod. 11-122 PO 120 G/R



Aluminium, Ø 150 mm

Cod. 11-135 PO 150 G

