



Adjustable gain multiswitch

4 TV-SAT tap outputs

**art. 15-455
MW54-15**



Ideal for the distribution of TV-SAT signals.

Realized with adjustable tap gain to ensure the equitable level of SAT signals at the sockets.

Three gain steps available: +5 dB, +10 dB e +15 dB.

The desired gain is selectable by acting on three step switch.

The terrestrial signal is in passive mixing to avoid any intermodulation problems.

The supply of the multiswitch and the LNB is provided by the SAT receiver, which also provides the control voltages for commutation.

The remote power supply from the multiswitch to the LNB is enabled on the V/L connector.

If more users aren't able to provide the correct power supply, it is recommended to use in the SAT system the inserting device (art. 15-503) with the power supply unit ALIM/M5-SAT (art. 15-501) and to connect it on V/L polarization.

Tap outputs with screw F-type connectors.

Characteristics

- Three possible gain settings selectable by switch with three positions
- Noise figure stable over the whole range of gain

- High isolation between inputs
- Equipped with screw F-type connectors
- Compatible with all OFFEL multiswitches

Code	15-455	
Item	MW54-15	
No. of SAT inputs	4	
No. of TV inputs	1	
No. of SAT outputs	4	
No. of TV outputs	1	
No. of TV-SAT tap outputs	4	
SAT tap gain	dB	+5, +10, +15
TV tap gain	dB	-16
SAT Loophthrough Loss	dB	1,5 Typ. 2 Max
TV Loophthrough Loss	dB	4,5 Typ. 5 Max
SAT Return Loss	dB	>10
TV Return Loss	dB	>10
Max absorbed current @13V	mA	75
Max remote supply current	mA	300
SAT frequencies	MHz	950÷2150
TV frequencies	MHz	47÷790
Max SAT input level	dB μ V	85
Min SAT input level	dB μ V	45
Inputs isolation	dB	>30
Outputs isolation	dB	>30
Outputs F connectors		screw F-type
Dimensions (LxWxH)	mm	90x27x90
Packaging dimensions (LxWxH)	mm	100x33x90
Packaging weight	Kg	0,202
Fit temperature	°C	-10 ÷ +55
Compliant to		EN 50083-2, EN 60065

Technical data refer to a temperature of 25 °C

Example of application

