



TV and SAT outlet

OP series

art. 17-302
OPT/A

Terminal outlet ideal for the distribution of terrestrial and satellite digital signals in single and centralized systems.

Uninsulated outlet with a directional passage of current.

Realized in shielded die-cast metal housing with IEC 9,5 male output connector.

Cable entry from the side, realized with shielded fixing clamp.

Compatible with the return channel signals.



Characteristics

- Realized in die-casting housing
- IEC 9,5 male output connector
- Cable entry from the side

Code	17-302	
Item	OPT/A	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	1,8
Tap loss SAT	dB ±1	2,6
Tap loss Ch.R	dB ±1	2
Return loss Ch. R	dB	>8
Passage of current		yes
Cable entry		from the bottom
Output connector		IEC 9,5
Dimensions (LxWxH)	mm	22x38x42
Fit temperature	°C	-10 ÷ +55
Compliant to		EN 55083-2, EN 50083-4, EN 60065, EN 60728-11

Technical data refer to a temperature of 25 °C

Operation scheme



Packaging		
Package		multi-pack
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	130x89x42
Packaging weight	Kg	0,45

