Data sheet






Optical boxes

for wall mounting of optical components

art. 19-444 FO-TT

Optical box to be used in under-roof spaces in multi-fiber building systems, as required by Law 164/2014.

It is located in a technical space under the roof. It is the collection point for services received by air.



Allows up to 24 fibers termination. Prepared for 12 SC or LC adapters.

Suitable for "Loose" cable, of distribution or preterminated with connectors.

It is equipped with

- · Anchor points for the traction device of cables
- Removable internal tray for simplify the housing of the adapters and relative accessiories
- Protections of the bending radius of the cables
- Cable-tighten for 3 cables
- Removable front cover with key lock
- No. 12 heat shrinkable joint covers
- Transit pipe
- · Accessories for wall mounting and cable ties

Code		19-444
Item		FO-TT
Dimensions (LxWxH)	mm	205 x 60 x 235
Weight	Kg	0,50
Type of connector compatible		SC simplex or LC duplex
No. port		12
Cable port		1
Cable exit		2
Material		ABS
Color		White
Working temperature	°C	-40 ÷ +60
Designed according to compliance		TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC601754, EN297-1
Compliant to		RoHS, REACH, SvHC

