Data sheet







UHF antenna with three cradles

TRIO+ Z HD series

art. 21-456B TRIO+ Z HD BIANCA





Designed to maximize the reception of DTT signals in the range E21÷E60 attenuating the LTE 800 MHz band without preventing the proper functioning of channel E60.

and EA

New high-performance dipole, meticulously designed to maximize performance, with innovative and practical design at the same time, with openable lid to ensure maximum weather resistance without sacrificing a smooth insertion of the F connector.



The three cradles structure and the mechanism of deployment ensure high efficiency, high gain and a quick and easy installation, being pre-assembled type antenna.

Al

Characteristics


- · High efficiency and high gain
- Quick and easy installation: pre-assembled antennas with mechanism of deployment
- Excellent value for Front-to-back Ratio
- Three cradles structure silver anodized
- Aluminium alloy 6101 rod elements
- Dipole with special attack for the insertion of the waterproof rubber cap



Code Item		21-456B TRIO+ Z HD BIANCA	
Channels		E21÷E60	
Maximum gain	dBi	17	
Front-to-back Ratio	dB	> 28	
Beamwidth (-3 dB) H/V	0	34 / 42	
Wind load @ 129 Km / h	N	110	
VSWR		< 1,2	
$\begin{array}{ c c c c c }\hline \text{Impedance} & & & & & & & & \\\hline \text{Dimensions (LxWxH)} & & & & & & \\\hline \end{array}$		75 1133x535x650	
Secondary cradles mm		12x18	
Reflector		solid aluminium rod with high mechanical sturdiness	
Dipole connector		F-type	
Mast clanp for masts max mm		Ø 60	
Horizontal and vertical polarization with tilt adjustment		included	


Packaging

Package	No. pieces	Dimensions LxWxH (mm)	Weight (Kg)
single pack	1	1170x125x185	2,8
multi-pack	4	1200x340x410	12.2



Directivity

The patterns shown represent measurements made in the horizontal plane at the center of the band.



Rev. 0 10.2014

