Data sheet









Outdoor TV mixer

broadband inputs L series

art. 22-059 MIX2L V-U

This outdoor TV mixer is ideal to combine the signals of two antennas and distribute them to the TV on

















This mixer is designed to optimize the reception of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48. The two inputs are so distributed:

• 1 VHF band input

a single cable.

• 1 UHF band input.

On request it can be provided with the possibility to enable the remote power supply.

Characteristics

· Shielded housing with screw F-type connectors

· Fixing accessory suitable for masts up to ø 60 mm included

| Code | | 22-059 |
|------------------------------|-------|----------------------|
| Item | | MIX2L V-U |
| No. of inputs | | 2 |
| No. of outputs | | 1 |
| Insertion loss | dB ±1 | < 4 |
| Inputs isolation | dB | > 23 |
| Dimensions (LxWxH) | mm | 77x50x85 |
| Packaging dimensions (LxWxH) | mm | 100x90x54 |
| Packaging weight | Kg | 0,13 |
| Fit temperature | °C | -10 ÷ +55 |
| Compliant to | | EN 55083-2, EN 60065 |

Technical data refer to a temperature of 25 °C

