



## Miscelatore TV per esterno

banda e canale serie LK

**art. 22-142**  
**MIX2LK V+4+2Can.U-5**

This outdoor TV mixer is particularly suitable to receive:

- from one direction, the channels of VHF band and band 4 plus two channels of band 5;
- from a second direction, the channels of the band 5, to the exclusion of the two channels received through the other input.

Designed to properly receive all the signals, including the two channels of band 5, avoiding any disturbances arising from the mixing of the two antennas.

It's designed for the reception of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

Created with calibration on request. When ordering you must specify:

- the last channel of the band 4 and the first of the band 5;
- the two UHF channels which you want to be included in V+4+2Can.U input.



### Characteristics

- Shielded housing with screw F-type connectors
- Using slide switches, a remote power supply can be provided on input connectors
- Fixing accessory suitable for masts up to  $\varnothing$  60 mm included

Code	22-142	
Item	MIX2LK V+4+2Can.U-5	
No. of inputs	2	
Ch. UHF insertion loss	dB $\pm 1$	$\leq 5$
UHF band insertion loss	dB $\pm 1$	$< 4$
Separation between bands	dB	$> 16$
Channel bandwidth	MHz $\pm 1$	9
Channel selectivity	dB	$> 16$
Dimensions (LxWxH)	mm	142x60x130
Packaging dimensions (LxWxH)	mm	145x60x140
Packaging weight	Kg	0,6
Fit temperature	$^{\circ}\text{C}$	$-10 \div +55$
Compliant to	EN 55083-2, EN 60065	

Technical data refer to a temperature of 25  $^{\circ}\text{C}$

### Example of application

