



Indoor TV-SAT demixer

DEM DIGIT series

art. 22-221
DEM TV-SAT DIGIT

This indoor TV-SAT demixer is ideal for demixing signals coming from a single-cable distribution (TV+SAT) into useful signals to the TV and the satellite receiver.

Characteristics

- The commutation control and tone switching are enable on SAT output.
- Realized in die-casting housing
- Equipped with shielded fixing clamps



Code	22-221	
Item	DEM TV-SAT DIGIT	
No. of TV-SAT inputs	1	
No. of TV outputs	1	
No. of SAT outputs	1	
TV frequencies	MHz	47÷862
SAT frequencies	MHz	950÷2150
Ch. R frequencies	MHz	5÷40
TV freq. insertion loss	dB ±1	2
SAT freq. insertion loss	dB ±1	2
Ch. R freq. insertion loss	dB ±1	0,8
Ch. R return loss	dB	> 15
Outputs isolation	dB	> 28
Dimensions (LxWxH)	mm	56x20x18
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 60065	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 130x61x42
Packaging weight	Kg 0,68

Example of application

