



## Indoor multiband amplifier broadband inputs MA series

**art. 26-022**  
**MA2/20 V-U**



Indoor multiband amplifier with broadband inputs, indicated for small size TV systems.

This amplifier is designed to optimize the amplification of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48

The two inputs are so distributed:

- 1 VHF band input;
- 1 UHF band input.

Each input is equipped with a coaxial attenuator (0÷20 dB) as level regulator and a switch to enable remote power supply.

### Characteristics

- Components with a high quality standard
- Shielded housing with screw F-type connectors
- Separate amplification for the VHF and UHF bands
- All broadband inputs are amplified
- Protection system against short circuits with LED notification

Code	26-022
Item	MA2/20 V-U
No. of inputs	2
No. of adjustments (0÷20 dB)	2
VHF band noise figure	dB 4
UHF band noise figure	dB 5
VHF band max output level*	dBμV 113
UHF band max output level*	dBμV 121
VHF input gain	dB ±2 24
UHF input gain	dB ±2 28
Max delivered current	mA 100
Remote power supply	Vdc 12
Max power consumption	VA 16
AC main tension	230 V~ ±10% 50Hz
Isolation class	II
Dimensions (LxWxH)	mm 200x100x60
Packaging dimensions (LxWxH)	mm 215x110x68
Packaging weight	Kg 0,86
Fit temperature	°C -10 ÷ +55
Compliant to EU directives	2014/53/UE, 2011/65/UE

\* Maximum output level measured with the method IM3 -35dBc 2 tones.  
Technical data refer to a temperature of 25 °C

### Example of application

