



Indoor multiband amplifier broadband and channel inputs MAK series

art. 26-089
MAK3/20 V-4-5+1Can.U



Indoor multiband amplifier with broadband and channel inputs, indicated for small size TV systems, ideal to receive:

- from one direction, the channels of band 5 plus one band 4 channel (e.g. ch. 25);
- from a second direction, all band 4 channels except the one received on the other input.

This amplifier is designed to optimize the amplification of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

The three inputs are so distributed:

- 1 VHF band input;
- 1 band 4 input;
- 1 band 5 + 1 band 4 channel input.

Each input is equipped with a coaxial attenuator (0÷20 dB) as level regulator and a switch to enable remote power supply, with the exception of 5+1Can.U input which is equipped with two coaxial attenuators (1 for the band 5 and 1 for the band 4 channel).

Created with calibration on request. When ordering you must specify:

- the last channel of the band 4 and the first of the band 5;
- the band 4 channel which you want to be included in 5+1Can.U input.

Characteristics

- Components with a high quality standard
- Shielded housing with screw F-type connectors
- Protection system against short circuits with LED notification

- All broadband and channel inputs are amplified
- Separate amplification for the VHF and UHF bands

Code	26-089
Item	MAK3/20 V-4-5+1Can.U
No. of inputs	3
No. of adjustments (0÷20 dB)	4
VHF band noise figure	dB 4
UHF band noise figure	dB 5
VHF band max output level*	dBμV 113
UHF band max output level*	dBμV 122
VHF input gain	dB ±2 21
Band 4 input gain	dB ±2 21
Band 5+Can. input gain	dB ±2 21-21
Max delivered current	mA 100
Remote power supply	Vdc 12
Max power consumption	VA 16
AC main tension	230 V~ ±10% 50Hz
Isolation class	II
Dimensions (LxWxH)	mm 244x100x60
Packaging dimensions (LxWxH)	mm 255x110x68
Packaging weight	Kg 0,96
Fit temperature	°C -10 ÷ +55
Compliant to EU directives	2014/53/UE, 2011/65/UE

* Maximum output level measured with the method IM3 -35dBc 2 tones.
Technical data refer to a temperature of 25 °C

Example of application

