



Indoor multiband amplifier broadband inputs MC series

art. 26-311
MS1/40 UHF

Indoor multiband amplifier with broadband inputs, indicated for medium/large size TV systems.

This amplifier is designed to optimize the amplification of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48

The input is equipped with a coaxial attenuators (0÷20 dB) as level regulators and with a switch to enable remote power supply.



Characteristics

- Components with a high quality standard
- Shielded housing with screw F-type connectors
- All broadband inputs are amplified
- Protection system against short circuits with LED notification

Code	26-311	
Item	MS1/40 UHF	
No. of inputs	1	
No. of adjustments (0÷20 dB)	1	
UHF band noise figure	dB	5
Tensione max di uscita UHF*	dBμV	125
UHF input gain	dB ±2	43
Max delivered current	mA	100
Remote power supply	Vcc	12
Max power consumption	VA	16
AC main tension	230 V~ ±10% 50Hz	
Isolation class	II	
Dimensions (LxWxH)	mm	200x100x60
Packaging dimensions (LxWxH)	mm	215x110x68
Packaging weight	Kg	0,86
Fit temperature	°C	-10 ÷ +55
Compliant to EU directives	2014/53/UE, 2011/65/UE	

* Maximum output level measured with the method IM3 -35dBc 2 tones.
Technical data refer to a temperature of 25 °C

Example of application

