



Indoor multiband amplifier with high output level FUSION FB series

art. 26-485 FB3/25 V-U-U

Indoor multiband amplifier with high output level, with broadband inputs, indicated for medium size TV systems.

This amplifier is designed to optimize the amplification of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

Protection system against short circuits with LED notification.
With three inputs, an output and a monitor output (-30 dB).

The three inputs are so distributed:

- 1 VHF band input;
- 2 UHF band inputs.

Each input is equipped with a coaxial attenuator for the gain adjustment (0÷20 dB) and a switch to enable remote power supply.

Shielded die-casting metal housing with screw F-type connectors.



Characteristics

- Components with a high quality standard
- High output level
- Separate amplification for VHF and UHF bands

Code	26-485
Item	FB3/25 V-U-U
N. of inputs	3
N. of adjustments	3
VHF band noise figure	dB 4
UHF band noise figure	dB 8
VHF band max output level*	dBμV 121
UHF band max output level*	dBμV 125
VHF band gain	dB ±2 26
UHF band gain	dB ±2 26
Max delivered current	mA 50
Remote power supply	Vdc 12
Max power consumption	VA 16
AC main tension	230 V~ ±10% 50Hz
Isolation class	II
Dimensions (LxWxH)	mm 245x150x50
Packaging dimensions (LxWxH)	mm 300x162x58
Packaging weight	Kg 1,37
Fit temperature	°C -10 ÷ +55
Compliant to EU directives	EN 55083-2, EN 60065

* Maximum output level measured with the method IM3 -35dBc 2 tones.
Technical data refer to a temperature of 25 °C

Example of application

