



Indoor multiband amplifier with high output level FUSION FB series

art. 26-499
FB4/35 V-4-5-U

Indoor multiband amplifier with high output level, with broadband inputs, indicated for medium size TV systems.

This amplifier is designed to optimize the amplification of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

Protection system against short circuits with LED notification.
 With four inputs, an output and a monitor output (- 30 dB).

The four inputs are so distributed:

- 1 VHF band input;
- 1 band 4 input;
- 1 band 5 input;
- 1 UHF band input.

Each input is equipped with a coaxial attenuator for the gain adjustment (0÷20 dB) and a switch to enable remote power supply.

Shielded die-casting metal housing with screw F-type connectors.

Created with calibration on request. When ordering you must specify the last channel of the band 4 and the first of the band 5.

Characteristics

- Components with a high quality standard
- High output level
- Separate amplification for VHF and UHF bands

Code	26-499
Item	FB4/35 V-4-5-U
N. of inputs	4
N. of adjustments	4
VHF band noise figure	dB
UHF band noise figure	dB
VHF band max output level*	dBμV
UHF band max output level*	dBμV
VHF band gain	dB ±2
4 input gain	dB ±2
5 input gain	dB ±2
UHF band gain	dB ±2
Max delivered current	mA
Remote power supply	Vdc
Max power consumption	VA
AC main tension	230 V~ ±10% 50Hz
Isolation class	II
Dimensions (LxWxH)	mm
Packaging dimensions (LxWxH)	mm
Packaging weight	Kg
Fit temperature	°C
Compliant to EU directives	2014/53/UE, 2011/65/UE

* Maximum output level measured with the method IM3 -35dBc 2 tones.
 Technical data refer to a temperature of 25 °C

Example of application

