



Indoor tap

DIGIT series

art. 27-172 P1-12 DIGIT

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and one tap output.

It is an indoor product, realized in die-casting housing with shielded fixing clamps.

Provided with a directional passage of current on the tap output.

Compatible with the signals for the return line.



Characteristics

- Realized in die-casting housing
- Passage of current on both the outputs
- One through-low loss output and one tap output

Code	27-172	
Item	P1-12 DIGIT	
No. derived outputs		1
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	12
Tap loss SAT	dB ±1	12
Tap loss Ch. R	dB ±1	12
Throughpass loss TV	dB ±1	1,4
Throughpass loss SAT	dB ±1	1,6
Throughpass loss Ch. R	dB ±1	2
Inversed loss TV	dB ±1	>28
Inversed loss SAT	dB ±1	>25
Inversed loss Ch. R	dB ±1	>26
Return loss Ch. R	dB	>10
Dimensions (LxWxH)	mm	56x20x18
Fit temperature	°C	-10 ÷ +55
Compliant to		EN 55083-2, EN 50083-4, EN 60065, EN 60728-11

Technical data refer to a temperature of 25 °C

Packaging		
Package		multi-pack
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	130x61x42
Packaging weight	Kg	0,65

Operation scheme

