



Indoor tap DIGIT series

art. 27-173 P1-16 DIGIT

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and one tap output.

It is an indoor product, realized in die-casting housing with shielded fixing clamps.

Provided with a directional passage of current on the tap output.

Compatible with the signals for the return line.



Characteristics

- Realized in die-casting housing
- Passage of current on both the outputs
- One through-low loss output and one tap output

| Code | 27-173 | |
|------------------------|---|-----------|
| Item | P1-16 DIGIT | |
| No. derived outputs | 1 | |
| Frequencies range | MHz | 5÷2150 |
| Tap loss TV | dB ±1 | 16 |
| Tap loss SAT | dB ±1 | 16,5 |
| Tap loss Ch. R | dB ±1 | 14,5 |
| Throughpass loss TV | dB ±1 | 0,6 |
| Throughpass loss SAT | dB ±1 | 1,2 |
| Throughpass loss Ch. R | dB ±1 | 1 |
| Inversed loss TV | dB ±1 | >35 |
| Inversed loss SAT | dB ±1 | >25 |
| Inversed loss Ch. R | dB ±1 | >28 |
| Return loss Ch. R | dB | >15 |
| Dimensions (LxWxH) | mm | 56x20x18 |
| Fit temperature | °C | -10 ÷ +55 |
| Compliant to | EN 55083-2, EN 50083-4, EN 60065, EN 60728-11 | |

Technical data refer to a temperature of 25 °C

| Packaging | | |
|------------------------------|------------|-----------|
| Package | multi-pack | |
| Quantity | pcs | 10 |
| Packaging dimensions (LxWxH) | mm | 130x61x42 |
| Packaging weight | Kg | 0,65 |

Operation scheme

