



Indoor tap

DIGIT series

art. 27-183 P2-20 DIGIT

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and two tap outputs, both with the same attenuation.

It is an indoor product, realized in die-casting housing with shielded fixing clamps.

Provided with a directional passage of current on both the tap outputs.

Compatible with the signals for the return line.



Characteristics

- Realized in die-casting housing
- Passage of current on both the outputs
- One through-low loss output and two tap outputs

Code	27-183	
Item	P2-20 DIGIT	
No. derived outputs	2	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	20
Tap loss SAT	dB ±1	20,5
Tap loss Ch. R	dB ±1	19,5
Throughpass loss TV	dB ±1	0,6
Throughpass loss SAT	dB ±1	1,3
Throughpass loss Ch. R	dB ±1	1
Derived separation TV	dB ±1	>23
Derived separation SAT	dB ±1	>26
Derived separation Ch. R	dB ±1	>19
Inversed loss TV	dB ±1	>32
Inversed loss SAT	dB ±1	>29
Inversed loss Ch. R	dB ±1	>30
Return loss Ch. R	dB	>18
Dimensions (LxWxH)	mm	56x20x18
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 130x61x42
Packaging weight	Kg 0,67

Operation scheme

