

## Indoor splitter

FUSION series

**art. 27-202**  
**CM2**

Ideal for the distribution of the TV-SAT signals in the 5÷2400 MHz frequency range.

It allows to divide the signal so that both the outputs have the same attenuation from one another.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on both the outputs.

Compatible with the signals for the return line.

### Characteristics


- Realized in die-casting housing with screw F-type connectors
- Two outputs with the same attenuation from one another
- Passage of current on both the outputs



Code	27-202	
Item	CM2	
No. outputs	2	
Frequencies range	MHz	5÷2400
Tap loss TV	dB	4,5
Tap loss SAT	dB	6
Tap loss Ch.R	dB	4
Outputs isolation TV	dB	22
Outputs isolation SAT	dB	22
Outputs isolation Ch. R	dB	20
Return loss Ch. R	dB	12
Connectors	screw F-type	
Dimensions (LxWxH)	mm	49x35x29
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

### Operation scheme



Packaging		
Package		multi-pack
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	184x55x65
Packaging weight	Kg	0,45

