



Indoor tap

FUSION series

art. 27-211
P1-8

Ideal for the distribution of the TV-SAT signals in the 5÷2400 MHz frequency range.

It has an input, a through-low loss output and one tap output.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Compatible with the signals for the return line.

Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and one tap output



Code	27-211	
Item	P1-8	
No. derived outputs	1	
Frequencies range	MHz	5÷2400
Tap loss TV	dB±1,5	11
Tap loss SAT	dB±1,5	11,5
Tap loss Ch. R	dB ±1	10
Throughpass loss TV	dB	1,8
Throughpass loss SAT	dB	2,8
Throughpass loss Ch. R	dB	1,5
Inversed loss TV	dB	20
Inversed loss SAT	dB	20
Inversed loss Ch. R	dB	20
Return loss Ch. R	dB	12
Connectors	screw F-type	
Dimensions (LxWxH)	mm	49x35x29
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging		
Package		multi-pack
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	184x55x65
Packaging weight	Kg	0,45

Operation scheme

