



Indoor tap

FUSION series

art. 27-213
P1-16

Ideal for the distribution of the TV-SAT signals in the 5÷2400 MHz frequency range.

It has an input, a through-low loss output and one tap output.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Compatible with the signals for the return line.

Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and one tap output



Code	27-213	
Item	P1-16	
No. derived outputs	1	
Frequencies range	MHz	5÷2400
Tap loss TV	dB ±1	18
Tap loss SAT	dB ±1	18
Tap loss Ch. R	dB ±1	18
Throughpass loss TV	dB	0,9
Throughpass loss SAT	dB	1,3
Throughpass loss Ch. R	dB	0,7
Inversed loss TV	dB	31
Inversed loss SAT	dB	22
Inversed loss Ch. R	dB	36
Return loss Ch. R	dB	12
Connectors	screw F-type	
Dimensions (LxWxH)	mm	49x35x29
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging		
Package	multi-pack	
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	184x55x65
Packaging weight	Kg	0,45

Operation scheme

