



Indoor tap

FUSION series

art. 27-243
P4-20

Ideal for the distribution of the TV-SAT signals in the 5÷2400 MHz frequency range.

It has an input, a through-low loss output and four tap outputs, all with the same attenuation.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Compatible with the signals for the return line.

Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and four tap outputs



Code	27-243	
Item	P4-20	
No. derived outputs	4	
Frequencies range	MHz	5÷2400
Tap loss TV	dB ±1	18
Tap loss SAT	dB ±1	18
Tap loss Ch. R	dB ±1	18
Throughpass loss TV	dB	1,5
Throughpass loss SAT	dB	2
Throughpass loss Ch. R	dB	1,2
Derived separation TV	dB	26
Derived separation SAT	dB	26
Derived separation Ch. R	dB	33
Inversed loss TV	dB	35
Inversed loss SAT	dB	30
Inversed loss Ch. R	dB	45
Return loss Ch. R	dB	≥10
Connectors	screw F-type	
Dimensions (LxWxH)	mm	71x35x29
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 184x72x65
Packaging weight	Kg 0,65

Operation scheme

