Data sheet









Antenna for vehicles

DISCOS series

art. 01-396 **DISCOS/E 5G**







Realized for the reception of DTT signals in the range E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of channel E48.



Removable plastic base, ideal for fixing on flat surfaces and also on mast. Fixing flange with 3 with Ø 9 mm holes.





Code		01-396
Item		DISCOS/E 5G
Color		white RAL 7035
Channels		E21÷E48
Gain	dB	20
Beamwidth (-3 dB) H/V	0	360
Current consumption	mA	70
VSWR		< 2
Impedance	Ω	75
Dipole connector		IEC 9,5
Polarization		horizontal
Base material		plastic support
Accessories for fixing on mast		included
Accessories for fixing on flat surfaces		included
Dimensions (LxWxH)	mm	250x250x120

Packaging

Package	No. pieces	Dimensions LxWxH (mm)	Weight (Kg)
single pack	1	270x265x165	1,6
multi-pack	6	560x285x525	11,2





Power supplies units for DISCOS series antennas (TO BE PURCHASED SEPARATELY)

Code		01-377	01-378	
Item		ALIM DISCOS CC	ALIM DISCOS/D	
No. inputs		1	1	
No. outputs		1	1	
No. trimmers for voltage regulation		1	1	
Maximum voltage delivered	V	8	8	
Powered by		main current 230 V~ ±10% 50 Hz	main current 230 V~ ±10% 50 Hz * or 12÷26 Vdc battery	
Isolation class		-	II	
Connectors		F screw type	F screw type	
Dimensions (LxWxH)	mm	120x95x47	120x95x47	
Fit temperature	°C	-10 ÷ +55	-10 ÷ +55	

^{*} If the 230 V~ current fails, it automatically draws the voltage from the battery.

Rev. 0 01.2023

