



Analog modulator multiband selfpowered - 1 in SCART

art. 07-861
MM 75

Device which allows the modulation of an audio/video signal (from cameras, SAT receivers, devices with composite video output, etc.) in an analog RF channel.

Being multiband allows the modulation of the output channel in the VHF, S or UHF bands.
Output channel controlled by PLL.

Audio and video signal levels are both adjustable by trimmers.
Equipped with coaxial attenuator (0÷20 dB) as output level regulator.
Equipped with an autodemixing A/V input with SCART connectors and an automixing RF output with screw F-type connectors.



| Code | 07-861 | |
|-------------------------------------|------------------------------|------------|
| Item | MM 75 | |
| No. of inputs | 1 | |
| No. of outputs | 1 | |
| No. of coaxial attenuators (0÷20dB) | 1 | |
| Output channels | E02÷E69 | |
| Standards | PAL B/G | |
| Max input level: | | |
| Audio | Vrms | 1 |
| Video (@ 75 Ω) | Vpp | 1 |
| Audio format | mono | |
| Max output level | dBμV | 75 |
| RF bypass insertion loss | dB | < 4 |
| Max power consumption | VA | 4 |
| AC main tension | 230 V~ ±10% 50Hz | |
| Isolation class | II | |
| A/V input connectors | SCART type | |
| RF output connectors | screw F type | |
| Dimensions (LxWxH) | mm | 125x170x50 |
| Packaging dimensions (LxWxH) | mm | 210x160x60 |
| Packaging weight | Kg | 0,67 |
| Fit temperature | °C | -10 ÷ +55 |
| Compliant to | EN 55013, EN 55020, EN 60065 | |

Technical data refer to a temperature of 25 °C

Example of application

