## Data sheet









## Outdoor TV mixer

broadband inputs L series

art. 22-079 **MIX4L V-4-5-U** 

















the TV on a single cable.

This mixer is designed to optimize the reception of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

This outdoor TV mixer is ideal to combine the signals of four different antennas and distribute them to

The four inputs are so distributed:

- 1 VHF band input
- 1 band 4 input
- 1 band 5 input
- 1 UHF band input.

On request it can be provided with the possibility to enable the remote power supply.

Available, on request, with resistive trimmers (0÷15 dB) as level regulators on inputs.

Created with calibration on request. When ordering you must specify the last channel of the band 4 and the first of the band 5.


## **Characteristics**

Shielded housing with screw F-type connectors

Fixing accessory suitable for masts up to ø 60 mm included

Code		22-079
Item		MIX4L V-4-5-U
No. of inputs		4
No. of outputs		1
Insertion loss for single band input	dB ±1	< 3
Insertion loss for overlapping band inputs	dB ±1	< 5
Inputs isolation	dB	> 20
Dimensions (LxWxH)	mm	87x48x105
Packaging dimensions (LxWxH)	mm	110x120x60
Packaging weight	Kg	0,21
Fit temperature	°C	-10 ÷ +55
Compliant to		EN 55083-2, EN 60065

Technical data refer to a temperature of 25 °C



Offel s.r.l.