



## Outdoor multiband amplifier 12÷15V broadband and channel inputs LCK series

### art. 24-219 LCK3/30 V-4-5+2Can.U

Outdoor multiband amplifier with broadband and channel inputs, indicated for medium size TV systems, ideal to receive:

- from one direction, the channels of band 5 plus two band 4 channels (e.g. ch. 25 and a local network ch.);
- from a second direction, all band 4 channels except the two channels received on the other input.

This amplifier is designed to optimize the amplification of DTT signals in the range E05÷E12+E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

The three inputs are so distributed:

- 1 VHF band input;
- 1 band 4 input;
- 1 band 5 + 2 band 4 channels input.

Each input is equipped with a coaxial attenuator (0÷20 dB) as level regulator and a switch to enable remote power supply, with the exception of 5+2Can.U input which is equipped with two coaxial attenuators (1 for the band 5 and 1 for the band 4 channels).

Created with calibration on request. When ordering you must specify:

- the last channel of the band 4 and the first of the band 5;
- the band 4 channels which you want to be included in 5+2Can.U input.

### Characteristics

- Components with a high quality standard
- Shielded housing with screw F-type connectors
- Separate amplification for the VHF and UHF bands
- All broadband inputs are amplified
- Fixing accessory suitable for masts up to ø 60 mm included

Code	24-219
Item	LCK3/30 V-4-5+2Can.U
No. of inputs	3
No. of adjustments (0÷20 dB)	4
VHF band noise figure	dB 4
UHF band noise figure	dB 5
VHF band max output level*	dBμV 114
UHF band max output level*	dBμV 123
VHF input gain	dB ±2 32
4 input gain	dB ±2 32
5+2Can. input gain	dB ±2 30-30
Absorbed current	mA 180
Supply voltage	Vdc 12÷15
Dimensions (LxWxH)	mm 142x60x130
Packaging dimensions (LxWxH)	mm 145x60x140
Packaging weight	Kg 0,5
Fit temperature	°C -10 ÷ +55
Compliant to EU directives	2014/53/UE, 2011/65/UE

\* Maximum output level measured with the method IM3 -35dBc 2 tones.  
Technical data refer to a temperature of 25 °C

### Example of application

