



Outdoor multiband amplifier 12÷15V broadband inputs Fusion Pro FPE series

art. 24-768
FPE20/30 U-U



Outdoor multiband amplifier with broadband inputs, indicated medium size TV systems.

This amplifier is designed to optimize the amplification of DTT signals in the range E21÷E48, attenuating the 700 MHz band without preventing the proper functioning of the channel E48.

Ideal for different system solutions thanks to a two-step selector that allows to set the maximum gain on the UHF band at 20 or 30 dB.

The two UHF band inputs are equipped with a trimmer for the gain adjustment 0÷15 dB and a switch to enable remote power supply.

Fully shielded die-casting metal housing with screw F-type connectors and tilting mechanism for an easy cable connection. Sturdy waterproof case in ABS plastic with housing for the insertion of cables. Fixing accessory suitable for masts up to Ø 60 mm included.


Characteristics

- 20 or 30 dB UHF band max gain selector
- High output level
- Components with a high quality standard

Code	24-768	
Item	FPE20/30 U-U	
No. of inputs	2	
No. of adjustments	2	
Noise figure	dB	6
Band max output level*	dBµV	125
UHF BAND GAIN SELECTOR	20 dB	30 dB
UHF inputs max gain	dB ±2	23 33
Absorbed current	mA	140
Supply voltage	Vdc	12÷15
Dimensions (LxWxH)	mm	132x55x107
Packaging dimensions (LxWxH)	mm	115x55x135
Packaging weight	Kg	0,345
Fit temperature	°C	0 ÷ +55
Compliant to EU directives	2014/53/UE, 2011/65/UE	

* Maximum output level measured with the method IM3 -35dBc 2 tones.
Technical data refer to a temperature of 25 °C

Example of application



Rev. 0 02.2026

