



Indoor splitter

DIGIT series

art. 27-084
CM4 DIGIT

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It allows to divide the signal so that all the outputs have the same attenuation from one another.

It is an indoor product, realized in die-casting housing with shielded fixing clamps.

Provided with a directional passage of current on all the outputs.

Compatible with the signals for the return line.




Characteristics

- Realized in die-casting housing
- Passage of current on both the outputs
- Four outputs with the same attenuation from one another

Code	27-084	
Item	CM4 DIGIT	
No. outputs	4	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	10
Tap loss SAT	dB ±1	10,5
Tap loss Ch.R	dB ±1	10
Outputs isolation TV	dB ±1	>22
Outputs isolation SAT	dB ±1	>19
Outputs isolation Ch. R	dB ±1	>14
Return loss Ch. R	dB	>5
Dimensions (LxWxH)	mm	72x20x18
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Operation scheme



Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 130x61x42
Packaging weight	Kg 0,66

