



Indoor splitter

DIGIT series

**art. 27-085
CM5 DIGIT**

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It allows to divide the signal so that all the outputs have the same attenuation from one another.

It is an indoor product, realized in die-casting housing with shielded fixing clamps.

Provided with a directional passage of current on all the outputs.

Compatible with the signals for the return line.



Characteristics

- Realized in die-casting housing
- Passage of current on both the outputs
- Five outputs with the same attenuation from one another

Code	27-085	
Item	CM5 DIGIT	
No. outputs	5	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	13
Tap loss SAT	dB ±1	13
Tap loss Ch.R	dB ±1	13
Outputs isolation TV	dB ±1	>20
Outputs isolation SAT	dB ±1	>18
Outputs isolation Ch. R	dB ±1	>14
Return loss Ch. R	dB	>6
Dimensions (LxWxH)	mm	72x20x18
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 130x80x42
Packaging weight	Kg 0,95

Operation scheme

