



Indoor splitter

FUSION series

**art. 27-202
CM2**

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It allows to divide the signal so that both the outputs have the same attenuation from one another.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on both the outputs.

Compatible with the signals for the return line.

Characteristics

- Realized in die-casting housing with screw F-type connectors
- Two outputs with the same attenuation from one another
- Passage of current on both the outputs



Code	27-202	
Item	CM2	
No. outputs	2	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	4
Tap loss SAT	dB ±1	5,5
Tap loss Ch.R	dB ±1	5
Outputs isolation TV	dB ±1	>20
Outputs isolation SAT	dB ±1	>18
Outputs isolation Ch. R	dB ±1	>15
Return loss Ch. R	dB	>8
Connectors	screw F-type	
Dimensions (LxWxH)	mm	53x39x26
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging		
Package		multi-pack
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	185x100x50
Packaging weight	Kg	0,56

Operation scheme

