



## Indoor splitter

FUSION series

**art. 27-208**  
**CM8**

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It allows to divide the signal so that all the outputs have the same attenuation from one another.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on all the outputs.

Compatible with the signals for the return line.

### Characteristics

- Realized in die-casting housing with screw F-type connectors
- Eight outputs with the same attenuation from one another
- Passage of current on all the outputs



| Code                    | 27-208  |           |
|-------------------------|---|-----------|
| Item                    | CM8   |           |
| No. outputs             | 8   |           |
| Frequencies range       | MHz   | 5÷2150    |
| Tap loss TV             | dB ±1   | 15        |
| Tap loss SAT            | dB ±1   | 13        |
| Tap loss Ch.R           | dB ±1   | 16        |
| Outputs isolation TV    | dB ±1   | >20       |
| Outputs isolation SAT   | dB ±1   | >20       |
| Outputs isolation Ch. R | dB ±1   | >14       |
| Return loss Ch. R       | dB  | >5        |
| Connectors              | screw F-type  |           |
| Dimensions (LxWxH)      | mm  | 119x39x26 |
| Fit temperature         | °C  | -10 ÷ +55 |
| Compliant to            | EN 55083-2,<br>EN 50083-4,<br>EN 60065, EN 60728-11 |           |

Technical data refer to a temperature of 25 °C

| Packaging                    |     |            |
|------------------------------|-----|------------|
| Package                      |     | multi-pack |
| Quantity                     | pcs | 10         |
| Packaging dimensions (LxWxH) | mm  | 185x150x50 |
| Packaging weight             | Kg  | 0,60       |

### Operation scheme

