



## Indoor tap FUSION series

**art. 27-223**  
**P2-16**

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and two tap outputs, both with the same attenuation.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on both the tap outputs.

Compatible with the signals for the return line.

### Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and two tap outputs
- Passage of current on both the outputs



Code	27-223	
Item	P2-16	
No. derived outputs	2	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	15,5
Tap loss SAT	dB ±1	16
Tap loss Ch. R	dB ±1	16
Throughpass loss TV	dB ±1	1,3
Throughpass loss SAT	dB ±1	1,7
Throughpass loss Ch. R	dB ±1	2,2
Derived separation TV	dB ±1	>20
Derived separation SAT	dB ±1	>18
Derived separation Ch. R	dB ±1	>19
Inversed loss TV	dB ±1	>30
Inversed loss SAT	dB ±1	>30
Inversed loss Ch. R	dB ±1	>25
Return loss Ch. R	dB	>12
Connectors	screw F-type	
Dimensions (LxWxH)	mm	53x39x26
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 185x100x50
Packaging weight	Kg 0,56

### Operation scheme

