



## Indoor tap FUSION series

**art. 27-224  
P2-20**

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and two tap outputs, both with the same attenuation.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on both the tap outputs.

Compatible with the signals for the return line.

### Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and two tap outputs
- Passage of current on both the outputs

Code	27-224
Item	P2-20
No. derived outputs	2
Frequencies range MHz	5÷2150
Tap loss TV dB ±1	20
Tap loss SAT dB ±1	20,5
Tap loss Ch. R dB ±1	19,5
Throughpass loss TV dB ±1	0,6
Throughpass loss SAT dB ±1	1,3
Throughpass loss Ch. R dB ±1	1
Derived separation TV dB ±1	>23
Derived separation SAT dB ±1	>26
Derived separation Ch. R dB ±1	>19
Inversed loss TV dB ±1	>32
Inversed loss SAT dB ±1	>29
Inversed loss Ch. R dB ±1	>30
Return loss Ch. R dB	>18
Connectors	screw F-type
Dimensions (LxWxH) mm	53x39x26
Fit temperature °C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity pcs	10
Packaging dimensions (LxWxH) mm	185x100x50
Packaging weight Kg	0,56

### Operation scheme

