



## Indoor tap FUSION series

**art. 27-234**  
**P3-24**

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and three tap outputs, all with the same attenuation.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on all the tap outputs.

Compatible with the signals for the return line.

### Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and three tap outputs
- Passage of current on all the outputs



Code	27-234	
Item	P3-24	
No. derived outputs	3	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	24
Tap loss SAT	dB ±1	25
Tap loss Ch. R	dB ±1	24
Throughpass loss TV	dB ±1	0,6
Throughpass loss SAT	dB ±1	1,4
Throughpass loss Ch. R	dB ±1	1
Derived separation TV	dB ±1	>25
Derived separation SAT	dB ±1	>20
Derived separation Ch. R	dB ±1	>28
Inversed loss TV	dB ±1	>37
Inversed loss SAT	dB ±1	>35
Inversed loss Ch. R	dB ±1	>37
Return loss Ch. R	dB	>18
Connectors	screw F-type	
Dimensions (LxWxH)	mm	75x39x26
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 185x150x50
Packaging weight	Kg 0,75

### Operation scheme

