



Indoor tap FUSION series

art. 27-242
P4-16

Ideal for the distribution of the TV-SAT signals in the 5÷2150 MHz frequency range.

It has an input, a through-low loss output and four tap outputs, all with the same attenuation.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on all the tap outputs.

Compatible with the signals for the return line.

Characteristics

- Realized in die-casting housing with screw F-type connectors
- One through-low loss output and four tap outputs
- Passage of current on all the outputs



Code	27-242	
Item	P4-16	
No. derived outputs	4	
Frequencies range	MHz	5÷2150
Tap loss TV	dB ±1	16
Tap loss SAT	dB ±1	16
Tap loss Ch. R	dB ±1	16
Throughpass loss TV	dB ±1	1,8
Throughpass loss SAT	dB ±1	3,1
Throughpass loss Ch. R	dB ±1	2,5
Derived separation TV	dB ±1	>20
Derived separation SAT	dB ±1	>18
Derived separation Ch. R	dB ±1	>19
Inversed loss TV	dB ±1	>27
Inversed loss SAT	dB ±1	>23
Inversed loss Ch. R	dB ±1	>25
Return loss Ch. R	dB	>15
Connectors	screw F-type	
Dimensions (LxWxH)	mm	75x39x26
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging	
Package	multi-pack
Quantity	pcs 10
Packaging dimensions (LxWxH)	mm 185x150x50
Packaging weight	Kg 0,75

Operation scheme

